

AMAX-5001

AMAX-5079

Smart Power Input Module with 4-ch DI

EtherCAT Extension



AMAX-5001



Specifications

General

- **Certification** CE, FCC class A
- **Connector** Pluggable 4P+8P push-in terminal (#24-16 AWG)
- **Enclosure** PC
- **Power Consumption** 2W@24V_{DC}
- **Protocol** EtherCAT
- **Transmission Rate** 100Mbps
- **LED Indicator** PWR, RUN, Power Diagnosis LED

Power Input

- **Rated Voltage** 24V_{DC} (± 20%)
- **Dual Power Input** Supported
- **Max Current on Bus** 2A
- **Diagnosis Function** Over/under voltage for input 1&2
Over current output on bus

Digital Input

- **Channels** 4
- **Digital Input** Wet Contact
Rated voltage: 24V_{DC}
Logic level 1: 10-30 V_{DC} and -10--30 V_{DC}
Logic level 0: -3-3 V_{DC}
- **Input Delay** From logic level 0 to 1: 4ms
From logic level 1 to 0: 4ms
- **Digital Filter** 3ms

Protection

- **Isolation Voltage** 2,000 V_{DC}

Environment

- **Operation Temperature** -25-60°C (vertical mounted)
- **Storage Temperature** -40-85°C
- **Relative Humidity** 95% (non-condense)

Ordering Information

- **AMAX-5001** Smart Power Input Module with 4DI



AMAX-5079



Specifications

General

- **Certification** CE, FCC class A
- **Connector** 1 x RJ45
- **Enclosure** PC
- **Power Consumption** N/A
- **Protocol** EtherCAT
- **Transmission Rate** 100Mbps
- **LED Indicator** N/A

EtherCAT Extension

- **Function** Conversion of EtherCAT to 100BASE-TX Ethernet for extension of the EtherCAT network
- **Cable** Ethernet/EtherCAT cable (min. Cat. 5), shielded
- **Distance between stations** Max. 100 m (100BASE-TX)
- **Bus Interface** 1 x RJ45
- **Power from bus** N/A

Protection

- **Isolation Voltage** 1,500 V_{DC} (LAN port)

Environment

- **Operation Temperature** -25-60°C (vertical mounted)
- **Storage Temperature** -40-85°C
- **Relative Humidity** 95% (non-condense)

Ordering Information

- **AMAX-5079** EtherCAT Extension