KEY TECHNOLOGY (CHINA) LIMITED 派训市键特电子有限公司

Head Office:B703,Building 1,Tianan Cyber Park,Huang Ge North Road,Longcheng Subdistrict,Long Gang District,ShenZhen,Guang Dong, P.R.China Factory ADD.:Floor 7, Building S8, Fenggang Tianan Cyber Park, No. 208 Fenggang Section, Dongshen Road, Fenggang Town, DongGuan, Guang Dong, P.R. China


Tel:+86 755 89239859,89230460,85232807 Fax:+86 755 89312576 E-mail:info@key-tek.cn,sales01@key-tek.cn Website:www.key-tek.cn,www.rugged-key.com

Model NO: K-TEK-M284-FN-IL-OEM

DESCRIPTION: 89 keys IP67 dynamic waterproof silicone rubber keyboard, with carbon-on-gold key switch 12 FN keys (F1, F2...F11, F12) on top line for easy operation, industrial PCB with carbon-on-gold key switch technology with long stroke (1.50mm) with extremely good tactile feeling for fast and accurate data input without any noise, durable coating & antimicrobial keyboard surface withstand to most chemicals and liquids under harsh environment, top panel mounting, industrial backlight optional.

Dimensions: 284.00mm x 109.00mm x 12.6mm (L x W x H)

Esc	F1	F2	F3	F4 F	5 F6	F7	F8	F9	F10	F11 F12	Num B SysR	g Scroll Lock	Pause Break
	1	@ 2	# 3	\$ 4	% 5	6	& 7 7	* 8 8	(9 9)*	- + =	Back Space ◀	Home
Tab	Q	W	E	R	Т	Y	U 4	5	0 6	P -	{]		PgUp
Caps Lock	A	S	D	F	G	Н	J	к	2 L	3 : +		Enter	PgDn
∱ Shi	ft 2	z] [x	c	V	3	N	MO	< ,	> · ?	/ 介Shift		End
Fn	Ctrl			Alt		245 J.	-)[Alt	Ctrl		Del 🔸		





後 KEY TECHNOLOGY (CHINA) LIMITED 深圳市键持电子有限公司

Head Office:B703,Building 1,Tianan Cyber Park,Huang Ge North Road,Longcheng Subdistrict,Long Gang District,ShenZhen,Guang Dong, P.R.China Factory ADD.: Floor 7, Building S8, Fenggang Tianan Cyber Park, No. 208 Fenggang Section, Dongshen Road, Fenggang Town, DongGuan, Guang Dong, P.R. China

Tel:+86 755 89239859,89230460,85232807 Fax:+86 755 89312576 E-mail:info@key-tek.cn,sales01@key-tek.cn Website:www.key-tek.cn,www.rugged-key.com

APPLICATIONS:

This ruggedized and compact design keyboard can be good for working in low-light areas, it is also available with optional LED backlighting. This keyboard is ideal for below wide applications:

MEDICAL: lab, hospital, clinic, dental, such as carts, diagnostic equipments, operation rooms, dialysis centers etc;

MATERIAL HANDLING: mobile keyboard, data entry, assembly line etc

MILITARY: Army, Navy, Air force

INDUSTRIAL: Industrial automation, pharmaceutical, oil and gas, food and beverage, clean or dirty manufacturing environments, warehouses

MAIN FEATURES:

Keyboard provides rugged, compact design, rugged construction for reliable functionality.

The keyboard lacks the crevices found between the keys of a regular keyboard, which is protected against dust, dirt, grease and corrosive liquid, which means it can withstand directed hose water, disinfectants, environmental contaminants and heavy industrial use.

Special durable-coating for excellent mechanical and chemical resistance.

With firm tactile key feel, key travel 1.50mm key travel.

Actuation Force: Square key: 1.2N+/-0.1N Rectangular key: 2N+/-0.1N

Ease of customizing with multiple languages, to accommodate foreign or custom variants.

PS/2, USB connection cables that plug directly into computer like keyboard operations.

Low-profile keys for easy cleaning

Key life: 5 millions

MECHANICAL DATA

Key: 89 keys Key top style: Protuberant rectangular keys with tactile feeling. More than Lifetime 5 million strokes G.W.: 0.80KGs Dimensions: 284.00mm x 109.00mm x 12.6mm (L x W x H)

ELECTRICAL DATA

Supply Voltage: +5V DC +/-5% Current Rating: 30mA (non-backlight) , 300mA (with backlight on) Lifespan> 5 years Switch Contact Material: Carbon-on-Gold key switch technology. Interface: PS2, USB available. Cable length: Standard 2.0m, customized length available. OS: All Windows, Linux, Unix, Mac OSX, Vxworks, Android, (U-cos--To be confirmed)

ENVIRONMENTAL ADAPTABILITY

Operating temperature:-20°C to +60°C Storage temperature: :-30°C to +70°C Saline mist: 96h, IEC60512-6 Damp heat test at +40°C: 21 days, IEC 60512-6 Dry heat test at +85°C: 10 days, IEC 60512-6 Operating RH: 100% Atmospheric pressure: 60-106Kpa Shock: 3 x 11 ms pulses of 50g on each of 3 axes





Head Office:B703,Building 1,Tianan Cyber Park,Huang Ge North Road,Longcheng Subdistrict,Long Gang District,ShenZhen,Guang Dong, P.R.China Factory ADD.:Floor 7, Building S8, Fenggang Tianan Cyber Park, No. 208 Fenggang Section, Dongshen Road, Fenggang Town, DongGuan, Guang Dong, P.R. China

Tel:+86 755 89239859,89230460,85232807 Fax:+86 755 89312576 E-mail:info@key-tek.cn,sales01@key-tek.cn Website:www.key-tek.cn,www.rugged-key.com

RELIABILITY

RoHS , CE, FCC Protection Level: IP67 Key Lifespan >5 million actuations MTBF >20000H MTTR <30min

