



## Specifications

System Mainboard	IB922
CPU	AMD G-Series; Quad-Core GX-415GA 1.5GHz
CPU Socket	FT3 BGA package
Chipset	SoC Integrated
Memory	1x DDR3-1600 MHz SO-DIMM, Single channel, Max. 8GB (Non-ECC)
Graphics	AMD Radeon™ HD8330E Graphics integrated in APU <ul style="list-style-type: none"> <li>• DirectX 11.1</li> <li>• Direct Compute 11</li> <li>• Open GL 4.0</li> <li>• OpenCL 1.1</li> <li>• UVD4.2 hardware Video Decoder –H.264, MPEG-2, VC-1, MPEG4 (DivX), and WMV</li> <li>• VCE 2.0 –Video conferencing, wireless display. H.264, SVC</li> </ul>
LAN	1x Realtek RTL8111H-CG Gigabit LAN controller
Expansion Slots	1x Mini PCI-E (full-size) 1x SIM card slot
I/O Interface	2x HDMI 1.4a 2x USB 3.0 ports 1x USB 2.0 port 1x RJ45 for LAN 1x RJ45 for RS232 2x Audio connectors for Line-in / Line-out 1x Power LED 1x Power button 1x DC jack
Auto Control and Monitoring	Watchdog Timer: 256 segments, 0, 1, 2...255 (sec/min)
Power Requirement	+12V DC-in
Construction	Aluminum + SGCC
Weight	0.9 kg (1.98 lbs)
Chassis Color	Black & white
Storage	1x mSATA
Power Supply	60W power adaptor
Mounting	Standard system bracket
Dimensions	190mm(W) x 130mm(D) x 19.5mm(H) 7.48"(W) x 5.12"(D) x 0.77"(H)
Operating Temperature	0°C ~ 45°C (32°F ~ 113°F)
Storage Temperature	-20°C ~ 80°C (-4°F ~ 176°F)
Relative Humidity	5~90% @ 45°C, (non-condensing)
Vibration	mSATA: 5 grms / 5~500Hz / random operation
Certification	CE, FCC Class-B, VCCI Class-B, cULus, LVD
Operating System	Windows® 7 (32/64-bit), Windows 8.1+ (32/64-bit) Win10 IoT Enterprise (64-bit) Windows 10 IoT Enterprise (64-bit) Window Embedded Standard 7 (32/64-bit) Window Embedded Standard 8 (32/64-bit) Linux Closed Source (64-bit), Linux Open Source (64-bit)

## Features

- iSMART intelligent energy-saving & Observer remote monitoring technologies
- 2nd Gen AMD Embedded G-Series SoC APU Processors
- SoC Integrated 80 Core™ DirectX 11.1 GPU in processor
- 2x HDMI 1.4a
- 1x DDR3-1600 SO-DIMM, Single channel, Max. 8GB
- 1x Mini PCI-E (full-size) for Wi-Fi, Bluetooth or 4G LTE options
- Fanless, super slim and compact design

## Ordering Information

SI-22-415	Signage Player with G-Series Quad-Core 1.5GHz APU, 4GB DDR3 SO-DIMM, 128GB mSATA, 60W power adaptor
SI-MK1	Mounting bracket
SI-1U-AD	1U Rackmount kit
HDMI Cable Holder	SI-22 HDMI bracket kit

## Dimensions

