

导轨式系列DIN-Rail Series

Features:

- High efficiency, high reliability and low cost
- Switch input voltage range choice
- 100% full load and machine test
- Protection characteristics: short circuit/overload
- Air cooling
- DIN RAIL type , easy to installation



QYR-60W

型号 Type	输出 Output	差值 Tolerance	范围 Range	效率 Efficiency
QYR-60W-12V	12V 0-4.5A	±1%	150mV	85%
QYR-60W-24V	24V 0-2.5A	±1%	200mV	88%

输入电压范围 AC input voltage range	85~264VAC,47~63HZ;120~370VDC	过电压保护 Over-voltage protection	115~135%
输入电流 Input current	1.5A/115V0.5A/230V	启动、上升、保持时间 Set up,rise, hold up time	800ms,600ms,50ms
冲击电流 AC inrush current	冷启动电流30A/115V 60A/230V Cold-start current 30A/115V 60A/230V	耐压性 Withstand voltage	1/P-O/P:1.5KvAC1 minute 1/P-FG:1.5KvAC1 minute 0/P-PG:0.5KvAC1 minute
漏电流 Leakage current	<1mA/240VAC	工作温度、湿度 Working temperature	-10℃~+60℃, 20%~90%RH
直流电压可调范围 DC adjustable range	额定输出电压的 ±10% ±10% rated output voltage	重量/包装 Weight/packing	0.28kg
过载保护 Over load protection	105~135%切断输出, 自动恢复 105~135% cut down output, auto-recovery		



QYR-100W

型号 Type	输出 Output	差值 Tolerance	范围 Range	效率 Efficiency
QYR-100W-12V	12V 0-7.5A	±1%	150mV	87%
QYR-100W-24V	24V 0-4.2A	±1%	200mV	88%

输入电压范围 AC input voltage range	85~264VAC,47~63HZ;120~370VDC	过电压保护 Over-voltage protection	115~135%
输入电流 Input current	1.5A/115V0.5A/230V	启动、上升、保持时间 Set up,rise, hold up time	800ms,600ms,50ms
冲击电流 AC inrush current	冷启动电流30A/115V 60A/230V Cold-start current 30A/115V 60A/230V	耐压性 Withstand voltage	1/P-O/P:1.5KvAC1 minute 1/P-FG:1.5KvAC1 minute 0/P-PG:0.5KvAC1 minute
漏电流 Leakage current	<1mA/240VAC	工作温度、湿度 Working temperature	-10℃~+60℃, 20%~90%RH
直流电压可调范围 DC adjustable range	额定输出电压的 ±10% ±10% rated output voltage	重量/包装 Weight/packing	0.3kg
过载保护 Over load protection	105~135%切断输出, 自动恢复 105~135% cut down output, auto-recovery		



QYR-150W

型号 Type	输出 Output	差值 Tolerance	范围 Range	效率 Efficiency
QYR-150W-24V	24V 0-6.2A	±1%	200mV	88%
QYR-150W-48V	24V 0-3.2A	±1%	200mV	88%

输入电压范围 AC input voltage range	85~264VAC,47~63HZ;120~370VDC	过电压保护 Over-voltage protection	115~135%
输入电流 Input current	1.5A/115V0.5A/230V	启动、上升、保持时间 Set up,rise, hold up time	800ms,600ms,50ms
冲击电流 AC inrush current	冷启动电流30A/115V 60A/230V Cold-start current 30A/115V 60A/230V	耐压性 Withstand voltage	1/P-O/P:1.5KvAC1 minute 1/P-FG:1.5KvAC1 minute 0/P-PG:0.5KvAC1 minute
漏电流 Leakage current	< 3.5mA/240VAC	工作温度、湿度 Working temperature	-10℃~+60℃, 20%~90%RH
直流电压可调范围 DC adjustable range	额定输出电压的 ±10% ±10% rated output voltage	重量/包装 Weight/packing	0.45kg
过载保护 Over load protection	105~135%切断输出, 自动恢复 105~135% cut down output, auto-recovery		