

导轨式系列DIN-Rail Series



Size:55.5*100*125.2mm

DR75W

型号 Type	输出 Output	差值 Tolerance	范围 Range	效率 Efficiency
DR-75-12	12V,0.0-6.3A	±2%	100mV	76%
DR-75-24	24V,0.0-3.2A	±1%	150mV	80%
DR-75-48	48V,0.0-1.6A	±1%	240mV	81%

输入电压范围 AC input voltage range	85~264VAC,47~63HZ;120~370VDC	过电压保护 Over-voltage protection	115~135%
输入电流 Input current	1.5A/115V0.5A/230V	启动、上升、保持时间 Set up, rise, hold up time	800ms,600ms,50ms
冲击电流 AC inrush current	冷启动电流30A/115V 60A/230V Cold-start current 30A/115V 60A/230V	耐压性 Withstand voltage	1/P-O/P:1.5KvAC1 minute 1/P-FG:1.5KvAC1 minute 0/P-PG:0.5KvAC1 minute
漏电流 Leakage current	< 3.5mA/240VAC	工作温度、湿度 Working temperature	-10℃~+60℃, 20%~90%RH
直流电压可调范围 DC adjustable range	额定输出电压的 ±10% ±10% rated output voltage	重量/包装 Weight/packing	0.6kg
过载保护 Over load protection	105~135%切断输出, 自动恢复 105~135% cut down output, auto-recovery		



Size:65.5*100*125.2mm

DR120W

型号 Type	输出 Output	差值 Tolerance	范围 Range	效率 Efficiency
DR-120W-12V	12V 0-10A	±1%	100mV	82%
DR-120W-24V	24V 0-5A	±1%	120mV	84%
DR-120W-48V	48V 0-2.5A	±1%	150mV	85%

输入电压范围 AC input voltage range	85~264VAC,47~63HZ;120~370VDC	过电压保护 Over-voltage protection	115~135%
输入电流 Input current	1.5A/115V0.75A/230V	启动、上升、保持时间 Set up, rise, hold up time	800ms,600ms,50ms
冲击电流 AC inrush current	冷启动电流30A/115V 60A/230V Cold-start current 30A/115V 60A/230V	耐压性 Withstand voltage	1/P-O/P:1.5KvAC1 minute 1/P-FG:1.5KvAC1 minute 0/P-PG:0.5KvAC1 minute
漏电流 Leakage current	<1mA/240VAC	工作温度、湿度 Working temperature	-10℃~+60℃, 20%~90%RH
直流电压可调范围 DC adjustable range	额定输出电压的 ±10% ±10% rated output voltage	重量/包装 Weight/packing	0.7kg
过载保护 Over load protection	105~135%切断输出, 自动恢复 105~135% cut down output, auto-recovery		



Size:125*100*125.2mm

DR240W

型号 Type	输出 Output	差值 Tolerance	范围 Range	效率 Efficiency
DR-240W-24V	24V 0-10A	±1%	120mV	85%
DR-240W-48V	48V 0-5A	±1%	150mV	86%

输入电压范围 AC input voltage range	85~264VAC,47~63HZ;120~370VDC	过电压保护 Over-voltage protection	115~135%
输入电流 Input current	1.5A/115V0.75A/230V	启动、上升、保持时间 Set up, rise, hold up time	800ms,600ms,50ms
冲击电流 AC inrush current	冷启动电流30A/115V 60A/230V Cold-start current 30A/115V 60A/230V	耐压性 Withstand voltage	1/P-O/P:1.5KvAC1 minute 1/P-FG:1.5KvAC1 minute 0/P-PG:0.5KvAC1 minute
漏电流 Leakage current	<1mA/240VAC	工作温度、湿度 Working temperature	-10℃~+60℃, 20%~90%RH
直流电压可调范围 DC adjustable range	额定输出电压的 ±10% ±10% rated output voltage	重量/包装 Weight/packing	1.2kg
过载保护 Over load protection	105~135%切断输出, 自动恢复 105~135% cut down output, auto-recovery		



Size: 22.5*90*100mm

MDR-10W

型号 Type	输出 Output	差值 Tolerance	范围 Range	效率 Efficiency
MDR-10-5	5V, 2A	±1.0%	80mV	77%
MDR-10-12	12V, 0.84A	±1.0%	120mV	81%
MDR-10-15	15V, 0.67A	±1.0%	120mV	81%
MDR-10-24	24V,0.42A	±1.0%	150mV	84%

输入电压范围 AC input voltage range	85~264VAC,47~63HZ;120~370VDC	过电压保护 Over-voltage protection	115~135%
输入电流 Input current	1.5A/115V0.75A/230V	启动、上升、保持时间 Set up, rise, hold up time	800ms,600ms,50ms
冲击电流 AC inrush current	冷启动电流30A/115V 60A/230V Cold-start current 30A/115V 60A/230V	耐压性 Withstand voltage	1/P-O/P:1.5KvAC1 minute 1/P-FG:1.5KvAC1 minute 0/P-PG:0.5KvAC1 minute
漏电流 Leakage current	<1mA/240VAC	工作温度、湿度 Working temperature	-10℃~+60℃, 20%~90%RH
直流电压可调范围 DC adjustable range	额定输出电压的 ±10% ±10% rated output voltage	重量/包装 Weight/packing	0.25kg
过载保护 Over load protection	105~135%切断输出, 自动恢复 105~135% cut down output, auto-recovery		

Always Try Our Best To do For You

导轨式系列DIN–Rail Series



Size: 22.5*90*100mm

		型号 Type	输出 Output	差值 Tolerance	范围 Range	效率 Efficiency
MDR-20W		MDR-20-5	5V, 3A	±1.0%	80mV	77%
		MDR-20-12	12V, 1.67A	±1.0%	120mV	81%
		MDR-20-15	15V, 0.67A	±1.0%	120mV	81%
		MDR-20-24	24V, 0.42A	±1.0%	150mV	84%
输入电压范围 AC input voltage range	85~264VAC, 47~63HZ; 120~370VDC		过电压保护 Over-voltage protection	115~135%		
输入电流 Input current	1.5A/115V0.75A/230V		启动、上升、保持时间 Set up, rise, hold up time	800ms, 600ms, 50ms		
冲击电流 AC inrush current	冷启动电流30A/115V 60A/230V Cold-start current 30A/115V 60A/230V		耐压性 Withstand voltage	1/P-O/P: 1.5KVAC1 minute 1/P-FG: 1.5KVAC1 minute 0/P-PG: 0.5KVAC1 minute		
漏电流 Leakage current	<1mA/240VAC		工作温度、湿度 Working temperature	-10℃~+60℃, 20%-90%RH		
直流电压可调范围 DC adjustable range	额定输出电压的 ±10% ±10% rated output voltage		重量/包装 Weight/packing	0.25kg		
过载保护 Over load protection	105~135%切断输出, 自动恢复 105~135% cut down output, auto-recovery					



Size: 40*90*100mm

		型号 Type	输出 Output	差值 Tolerance	范围 Range	效率 Efficiency
MDR-40W		MDR-40W-5V	5V 0-6A	±1%	80mV	78%
		MDR-40W-12V	12V 0-3.33A	±1%	120mV	84%
		MDR-40W-24V	24V 0-1.7A	±1%	150mV	85%
输入电压范围 AC input voltage range	85~264VAC, 47~63HZ; 120~370VDC		过电压保护 Over-voltage protection	115~135%		
输入电流 Input current	1.5A/115V0.75A/230V		启动、上升、保持时间 Set up, rise, hold up time	800ms, 600ms, 50ms		
冲击电流 AC inrush current	冷启动电流30A/115V 60A/230V Cold-start current 30A/115V 60A/230V		耐压性 Withstand voltage	1P-O/P: 1.5KvAC1 minute 1P-FG: 1.5KvAC1 minute 0/P-PG: 0.5KvAC1 minute		
漏电流 Leakage current	<1mA/240VAC		工作温度、湿度 Working temperature	-10℃~+60℃, 20%~90%RH		
直流电压可调范围 DC adjustable range	额定输出电压的 ±10% ±10% rated output voltage		重量/包装 Weight/packing	0.4kg		
过载保护 Over load protection	105~135%切断输出, 自动恢复 105~135% cut down output, auto-recovery					



Size: 40*90*100mm

		型号 Type	输出 Output	差值 Tolerance	范围 Range	效率 Efficiency
		MDR-60W-5V	5V 0-10A	±1%	78mV	78%
MDR-60W		MDR-60W-12V	12V 0-5A	±1%	120mV	86%
		MDR-60W-24V	24V 0-2.5A	±1%	150mV	88%
		MDR-60W-48V	24V 0-1.25A	±1%	200mV	87%
输入电压范围 AC input voltage range	85~264VAC, 47~63HZ; 120~370VDC		过电压保护 Over-voltage protection		115~135%	
输入电流 Input current	1.5A/115V0.75A/230V		启动、上升、保持时间 Set up, rise, hold up time		800ms, 600ms, 50ms	
冲击电流 AC inrush current	冷启动电流30A/115V 60A/230V Cold-start current 30A/115V 60A/230V		耐压性 Withstand voltage		1/P-O/P: 1.5KvAC1 minute 1/P-FG: 1.5KvAC1 minute 0/P-PG: 0.5KvAC1 minute	
漏电流 Leakage current	<1mA/240VAC		工作温度、湿度 Working temperature		-10℃~+60℃, 20%-90%RH	
直流电压可调范围 DC adjustable range	额定输出电压的 ±10% ±10% rated output voltage		重量/包装 Weight/packing		0.4kg	
过载保护 Over load protection	105~135%切断输出, 自动恢复 105~135% cut down output, auto-recovery					



Size: 55*90*100mm

型号 Type		输出 Output	差值 Tolerance	范围 Range	效率 Efficiency
		MDR-100W-12V	12V 0-7.5A	±2%	120mV 82%
		MDR-100W-24V	24V 0-4A	±1%	150mV 84%
		MDR-100W-48V	48V 0-2A	±1%	200mV 85%
输入电压范围 AC input voltage range	85~264VAC, 47~63HZ; 120~370VDC		过电压保护 Over-voltage protection	115~135%	
输入电流 Input current	1.5A/115V0.75A/230V		启动、上升、保持时间 Set up, rise, hold up time	800ms, 600ms, 50ms	
冲击电流 AC inrush current	冷启动电流30A/115V 60A/230V Cold-start current 30A/115V 60A/230V		耐压性 Withstand voltage	1/P-O/P: 1.5KvAC1 minute 1/P-FG: 1.5KvAC1 minute 0/P-PG: 0.5KvAC1 minute	
漏电流 Leakage current	<1mA/240VAC		工作温度、湿度 Working temperature	-10℃~+60℃, 20%~90%RH	
直流电压可调范围 DC adjustable range	额定输出电压的 ±10% ±10% rated output voltage		重量/包装 Weight/packing	0.6kg	
过载保护 Over load protection	105~135%切断输出, 自动恢复 105~135% cut down output, auto-recovery				