

Rugged Handheld EM-T40





Functions

- Support for Android 11 system
- Optional 4G all network communication, WiFi, Bluetooth and other communication modes
- Equipped with 4500mAh large capacity battery, the machine has a endurance of 7 hours
- IP65 high protection level, in accordance with MIL-STD-810G
- Support GPS, Glonass, beidou(G+G+B), more accurate positioning
- With rear 13MP auto focus camera, you can easily collect your images and video information
- 2D, NFC and other functional modules to meet the application needs of multiple industries

Product Six Views



Specification Parameter

Basic parameters		Performance parameter	
Dimension	162.4 x 72.8 x 19.4mm	CPU	MTK OCTA Core
Weight	250g	OS	Android 11
Device Color	black	RAM	4GB
LCD	4 inch IPS 16:9, 480x800, 300nits	ROM	64GB
Touch Panel	5 point G+FF capacitive touch screen Corning [®] Gorilla [®] Glass	Battery	
Camera	Rear 13.0MP	Capacity	3.8V/4500mAh
I/O	USB Type–C x 1, TF Card x 1 max: 128G, SIM Card x 1 (Two out of three card holder), 6Pin back shell x 1, 2Pin machine buttom x 1	Туре	External removable lithium ion battery
		Endurance	7hrs (default 50% volumn, default 200 lumens brightness, play1080P video)
Power	AC100V ~ 240V, 50Hz/60Hz, Output DC 5V/2A	Reliability	
Communication		Operate Temperature	–10 °C ~ 55 °C
WIFI	WiFi 802.11 a/b/g/n/ac (2.4G+5G)	Store Temperature	−20 °C ~ 60 °C
Bluetooth	BT5.0	Humidity	95% Non-Condensing
4G (Optional)	GSM B2/B3/B5/B8 WCDMA B1/B2/B5/B8 TDS B34/B39 FDD B1/B2/B3/B4/B5/B7/B8/B13/B17/B20/B28AB TDD B38/B39/B40/B41	Rugged Feature	IP65 certified, MIL-STD-810G certified
		Drop Height	1.2m
		Data Collection	
GNSS	Built-in GPS, Glonass, beidou(G+G+B)	NFC	Built-in, 13.56MHz, ISO/IEC 14443A/B, ISO/IEC 15693, ISO/IEC 18092
		2D	Optional, EM80, 4710, EM03

Application Range

The handheld terminal with RFID UHF technology is widely used, which can meet the application in retail, storage material management, finance, express delivery, medical and other fields.

P

0





Market

in





Express Industry

Pharmacy Management



Tel: +86–(0)755–2372 2880 Web: www.emdoorrugged.com Email: marketing.info@emdoor.com

@emdoorrugged