

导轨式系列DIN-Rail Series



Size:25.5*93*56mm

DR15W

型号 Type	输出 Output	差值 Tolerance	范围 Range	效率 Efficiency
DR-15-5	5V, 2.4A	±2.0%	80mV	77%
DR-15-12	12V, 1.25A	±1.0%	200mV	84%
DR-15-15	15V, 1A	±1.0%	240mV	84%
DR-15-24	24V, 0.63A	±1.0%	480mV	84%

输入电压范围 AC input voltage range	85~264VAC, 47~63HZ; 120~370VDC	过电压保护 Over-voltage protection	115~135%
输入电流 Input current	1.5A/115V0.75A/230V	启动、上升、保持时间 Set up, rise, hold up time	800ms, 600ms, 50ms
冲击电流 AC inrush current	冷启动电流30A/115V 60A/230V Cold-start current 30A/115V 60A/230V	耐压性 Withstand voltage	1/P-O/P: 1.5KvAC 1 minute 1/P-FG: 1.5KvAC 1 minute 0/P-PG: 0.5KvAC 1 minute
漏电流 Leakage current	<1mA/240VAC	工作温度、湿度 Working temperature	-10℃~+60℃, 20%~90%RH
直流电压可调范围 DC adjustable range	额定输出电压的 ±10% ±10% rated output voltage	重量/包装 Weight/packing	0.15kg
过载保护 Over load protection	105~135%切断输出, 自动恢复 105~135% cut down output, auto-recovery		



Size:97*78*55mm

DR30W

型号 Type	输出 Output	差值 Tolerance	范围 Range	效率 Efficiency
DR-30-12	12V, 0~2.5A	±2%	150mV	77%
DR-30-15	15V, 0~2A	±1%	150mV	77%
DR-30-24	24V, 0~1.25A	±1%	200mV	82%

输入电压范围 AC input voltage range	85~264VAC, 47~63HZ; 120~370VDC	过电压保护 Over-voltage protection	115~135%
输入电流 Input current	1.5A/115V0.75A/230V	启动、上升、保持时间 Set up, rise, hold up time	800ms, 600ms, 50ms
冲击电流 AC inrush current	冷启动电流30A/115V 60A/230V Cold-start current 30A/115V 60A/230V	耐压性 Withstand voltage	1/P-O/P: 1.5KvAC 1 minute 1/P-FG: 1.5KvAC 1 minute 0/P-PG: 0.5KvAC 1 minute
漏电流 Leakage current	<1mA/240VAC	工作温度、湿度 Working temperature	-10℃~+60℃, 20%~90%RH
直流电压可调范围 DC adjustable range	额定输出电压的 ±10% ±10% rated output voltage	重量/包装 Weight/packing	0.3kg
过载保护 Over load protection	105~135%切断输出, 自动恢复 105~135% cut down output, auto-recovery		



Size:97*78*55mm

DR45W

型号 Type	输出 Output	差值 Tolerance	范围 Range	效率 Efficiency
DR-45-12	12V, 0.0~3.75A	±1%	200mV	77%
DR-45-15	15V, 0.0~3A	±1%	240mV	77%
DR-45-24	24V, 0.0~1.9A	±1%	480mV	80%

输入电压范围 AC input voltage range	85~264VAC, 47~63HZ; 120~370VDC	过电压保护 Over-voltage protection	115~135%
输入电流 Input current	1.5A/115V0.5A/230V	启动、上升、保持时间 Set up, rise, hold up time	800ms, 600ms, 50ms
冲击电流 AC inrush current	冷启动电流30A/115V 60A/230V Cold-start current 30A/115V 60A/230V	耐压性 Withstand voltage	1/P-O/P: 1.5KvAC 1 minute 1/P-FG: 1.5KvAC 1 minute 0/P-PG: 0.5KvAC 1 minute
漏电流 Leakage current	<1mA/240VAC	工作温度、湿度 Working temperature	-10℃~+60℃, 20%~90%RH
直流电压可调范围 DC adjustable range	额定输出电压的 ±10% ±10% rated output voltage	重量/包装 Weight/packing	0.3kg
过载保护 Over load protection	105~135%切断输出, 自动恢复 105~135% cut down output, auto-recovery		



Size:97*78*55mm

DR60W

型号 Type	输出 Output	差值 Tolerance	范围 Range	效率 Efficiency
DR-60-12	12V, 0~5A	±2%	150mV	77%
DR-60-15	15V, 0~4A	±1%	150mV	77%
DR-60-24	24V, 0~2.5A	±1%	200mV	82%
DR-60-18	18V 0~3A	±1%	180mV	78%

输入电压范围 AC input voltage range	85~264VAC, 47~63HZ; 120~370VDC	过电压保护 Over-voltage protection	115~135%
输入电流 Input current	1.5A/115V0.5A/230V	启动、上升、保持时间 Set up, rise, hold up time	800ms, 600ms, 50ms
冲击电流 AC inrush current	冷启动电流30A/115V 60A/230V Cold-start current 30A/115V 60A/230V	耐压性 Withstand voltage	1/P-O/P: 1.5KvAC 1 minute 1/P-FG: 1.5KvAC 1 minute 0/P-PG: 0.5KvAC 1 minute
漏电流 Leakage current	<1mA/240VAC	工作温度、湿度 Working temperature	-10℃~+60℃, 20%~90%RH
直流电压可调范围 DC adjustable range	额定输出电压的 ±10% ±10% rated output voltage	重量/包装 Weight/packing	0.3kg
过载保护 Over load protection	105~135%切断输出, 自动恢复 105~135% cut down output, auto-recovery		

导轨式系列DIN-Rail Series



Size:55.5*100*125.2mm

DR75W

型号 Type	输出 Output	差值 Tolerance	范围 Range	效率 Efficiency
DR-75-12	12V,0.0-6.3A	±2%	100mV	76%
DR-75-24	24V,0.0-3.2A	±1%	150mV	80%
DR-75-48	48V,0.0-1.6A	±1%	240mV	81%

输入电压范围 AC input voltage range	85~264VAC,47~63HZ;120~370VDC	过电压保护 Over-voltage protection	115~135%
输入电流 Input current	1.5A/115V0.5A/230V	启动、上升、保持时间 Set up, rise, hold up time	800ms,600ms,50ms
冲击电流 AC inrush current	冷启动电流30A/115V 60A/230V Cold-start current 30A/115V 60A/230V	耐压性 Withstand voltage	1/P-O/P:1.5KvAC1 minute 1/P-FG:1.5KvAC1 minute 0/P-PG:0.5KvAC1 minute
漏电流 Leakage current	< 3.5mA/240VAC	工作温度、湿度 Working temperature	-10℃~+60℃, 20%~90%RH
直流电压可调范围 DC adjustable range	额定输出电压的 ±10% ±10% rated output voltage	重量/包装 Weight/packing	0.6kg
过载保护 Over load protection	105~135%切断输出, 自动恢复 105~135% cut down output, auto-recovery		



Size:65.5*100*125.2mm

DR120W

型号 Type	输出 Output	差值 Tolerance	范围 Range	效率 Efficiency
DR-120W-12V	12V 0-10A	±1%	100mV	82%
DR-120W-24V	24V 0-5A	±1%	120mV	84%
DR-120W-48V	48V 0-2.5A	±1%	150mV	85%

输入电压范围 AC input voltage range	85~264VAC,47~63HZ;120~370VDC	过电压保护 Over-voltage protection	115~135%
输入电流 Input current	1.5A/115V0.75A/230V	启动、上升、保持时间 Set up, rise, hold up time	800ms,600ms,50ms
冲击电流 AC inrush current	冷启动电流30A/115V 60A/230V Cold-start current 30A/115V 60A/230V	耐压性 Withstand voltage	1/P-O/P:1.5KvAC1 minute 1/P-FG:1.5KvAC1 minute 0/P-PG:0.5KvAC1 minute
漏电流 Leakage current	<1mA/240VAC	工作温度、湿度 Working temperature	-10℃~+60℃, 20%~90%RH
直流电压可调范围 DC adjustable range	额定输出电压的 ±10% ±10% rated output voltage	重量/包装 Weight/packing	0.7kg
过载保护 Over load protection	105~135%切断输出, 自动恢复 105~135% cut down output, auto-recovery		



Size:125*100*125.2mm

DR240W

型号 Type	输出 Output	差值 Tolerance	范围 Range	效率 Efficiency
DR-240W-24V	24V 0-10A	±1%	120mV	85%
DR-240W-48V	48V 0-5A	±1%	150mV	86%

输入电压范围 AC input voltage range	85~264VAC,47~63HZ;120~370VDC	过电压保护 Over-voltage protection	115~135%
输入电流 Input current	1.5A/115V0.75A/230V	启动、上升、保持时间 Set up, rise, hold up time	800ms,600ms,50ms
冲击电流 AC inrush current	冷启动电流30A/115V 60A/230V Cold-start current 30A/115V 60A/230V	耐压性 Withstand voltage	1/P-O/P:1.5KvAC1 minute 1/P-FG:1.5KvAC1 minute 0/P-PG:0.5KvAC1 minute
漏电流 Leakage current	<1mA/240VAC	工作温度、湿度 Working temperature	-10℃~+60℃, 20%~90%RH
直流电压可调范围 DC adjustable range	额定输出电压的 ±10% ±10% rated output voltage	重量/包装 Weight/packing	1.2kg
过载保护 Over load protection	105~135%切断输出, 自动恢复 105~135% cut down output, auto-recovery		



Size: 22.5*90*100mm

MDR-10W

型号 Type	输出 Output	差值 Tolerance	范围 Range	效率 Efficiency
MDR-10-5	5V, 2A	±1.0%	80mV	77%
MDR-10-12	12V, 0.84A	±1.0%	120mV	81%
MDR-10-15	15V, 0.67A	±1.0%	120mV	81%
MDR-10-24	24V,0.42A	±1.0%	150mV	84%

输入电压范围 AC input voltage range	85~264VAC,47~63HZ;120~370VDC	过电压保护 Over-voltage protection	115~135%
输入电流 Input current	1.5A/115V0.75A/230V	启动、上升、保持时间 Set up, rise, hold up time	800ms,600ms,50ms
冲击电流 AC inrush current	冷启动电流30A/115V 60A/230V Cold-start current 30A/115V 60A/230V	耐压性 Withstand voltage	1/P-O/P:1.5KvAC1 minute 1/P-FG:1.5KvAC1 minute 0/P-PG:0.5KvAC1 minute
漏电流 Leakage current	<1mA/240VAC	工作温度、湿度 Working temperature	-10℃~+60℃, 20%~90%RH
直流电压可调范围 DC adjustable range	额定输出电压的 ±10% ±10% rated output voltage	重量/包装 Weight/packing	0.25kg
过载保护 Over load protection	105~135%切断输出, 自动恢复 105~135% cut down output, auto-recovery		