



DT-TB

Stainless Steel Optical Trackball

The DT-TB from iKey® offers solid-state laser trackball technology in a completely sealed and waterproof enclosure. Designed to meet NEMA 4X protection, the DT-TB's 38-mm trackball sits inside polycarbonate housing with a stainless steel case. The trackball is easily removable for convenience cleaning, while an adjustable tension ring ensures the proper amount of trackball smoothness for any user. In addition, the DT-TB features sealed stainless steel switches, including a programmable button.

Features:

Adjustable Tension Ring

ESD Safe

PS/2 or USB configurations available

Removable Ball

Stainless Steel Case

Product Code DT-TB

CERTIFICATIONS	NEMA 4X UL60950, FCC Part 15 Class B
SHOCK	3x11 ms pulses of 50g on each of 3 axes
CABLE	LENGTH: 10' straight (3 m) DESIGN: PS/2 or USB Cables
VIBRATION	POWER SPECTRAL DENSITY: 0.04g/Hz FREQUENCY RANGE: 20Hz - 2 kHz DURATION OF TEST PER AXIS: 3 hours
POWER	PS/2: 45mA@5V (from Mouse port) USB: 45mA@5V (from CPU port)
COMPATABILITY	PS/2: All Windows Operating Systems USB: All Windows and Macintosh OS
TEMPERATURE RANGE	STORAGE: -40C to +85C (-40F to 185F) OPERATING: 0C to +55C (32F to 131F)
WEIGHT	1.5 lbs (0.68 kg)
WARRANTY	1 year limited warranty
DIMENSIONS	4.0" x 6.0" x 2.0" (w-h-d) 101.6mm x 152.4mm x 50.8mm
MODEL NUMBERS	DT-TB-PS/2: with PS/2 cable DT-TB-USB with USB Cable