

NDR Series



Size: 32*125.2*102mm

NDR-75W

型号 Type	输出 Output	差值 Tolerance	范围 Range	效率 Efficiency
NDR-75W-12V	12V 0-6.3A	±2%	80mV	87%
NDR-75W-24V	24V 0-3.2A	±1%	120mV	88%
NDR-75W-48V	48V 0-1.6A	±1%	150mV	89%

输入电压范围 AC input voltage range	85~264VAC, 47~63HZ; 120~370VDC	过电压保护 Over-voltage protection	115~135%
输入电流 Input current	1.5A/115V0.75A/230V	启动、上升、保持时间 Set up, rise, hold up time	800ms, 600ms, 50ms
冲击电流 AC inrush current	冷启动电流30A/115V 60A/230V Cold-start current 30A/115V 60A/230V	耐压性 Withstand voltage	1/P-O/P: 1.5KvAC1 minute 1/P-FG: 1.5KvAC1 minute 0/P-PG: 0.5KvAC1 minute
漏电流 Leakage current	<1mA/240VAC	工作温度、湿度 Working temperature	-10℃~+60℃, 20%~90%RH
直流电压可调范围 DC adjustable range	额定输出电压的 ±10% ±10% rated output voltage	重量/包装 Weight/packing	0.45kg
过载保护 Over load protection	105~135%切断输出, 自动恢复 105~135% cut down output, auto-recovery		



Size: 32*125.2*102mm

NDR-120W

型号 Type	输出 Output	差值 Tolerance	范围 Range	效率 Efficiency
NDR-120W-12V	12V 0-10A	±2%	100mV	85%
NDR-120W-24V	24V 0-5A	±1%	120mV	88%
NDR-120W-48V	48V 0-2.5A	±1%	120mV	93%

输入电压范围 AC input voltage range	85~264VAC, 47~63HZ; 120~370VDC	过电压保护 Over-voltage protection	115~135%
输入电流 Input current	1.5A/115V0.75A/230V	启动、上升、保持时间 Set up, rise, hold up time	800ms, 600ms, 50ms
冲击电流 AC inrush current	冷启动电流30A/115V 60A/230V Cold-start current 30A/115V 60A/230V	耐压性 Withstand voltage	1/P-O/P: 1.5KvAC1 minute 1/P-FG: 1.5KvAC1 minute 0/P-PG: 0.5KvAC1 minute
漏电流 Leakage current	<1mA/240VAC	工作温度、湿度 Working temperature	-10℃~+60℃, 20%~90%RH
直流电压可调范围 DC adjustable range	额定输出电压的 ±10% ±10% rated output voltage	重量/包装 Weight/packing	0.5kg
过载保护 Over load protection	105~135%切断输出, 自动恢复 105~135% cut down output, auto-recovery		



Size: 40*90*100mm

NDR-240W

型号 Type	输出 Output	差值 Tolerance	范围 Range	效率 Efficiency
NDR-240W-24V	24V 0-10A	±2%	120mV	88%
NDR-240W-48V	48V 0-5A	±0.5%	150mV	90%

输入电压范围 AC input voltage range	85~264VAC, 47~63HZ; 120~370VDC	过电压保护 Over-voltage protection	115~135%
输入电流 Input current	1.5A/115V0.75A/230V	启动、上升、保持时间 Set up, rise, hold up time	800ms, 600ms, 50ms
冲击电流 AC inrush current	冷启动电流30A/115V 60A/230V Cold-start current 30A/115V 60A/230V	耐压性 Withstand voltage	1/P-O/P: 1.5KvAC1 minute 1/P-FG: 1.5KvAC1 minute 0/P-PG: 0.5KvAC1 minute
漏电流 Leakage current	<1mA/240VAC	工作温度、湿度 Working temperature	-10℃~+60℃, 20%~90%RH
直流电压可调范围 DC adjustable range	额定输出电压的 ±10% ±10% rated output voltage	重量/包装 Weight/packing	0.76kg
过载保护 Over load protection	105~135%切断输出, 自动恢复 105~135% cut down output, auto-recovery		



Size: 85.5*125.2*128.5mm

NDR-480W

型号 Type	输出 Output	差值 Tolerance	范围 Range	效率 Efficiency
NDR-480W-24V	24V 0-20A	±1%	200mV	91%
NDR-480W-48V	48V 0-10A	±1%	250mV	93%

输入电压范围 AC input voltage range	85~264VAC, 47~63HZ; 120~370VDC	过电压保护 Over-voltage protection	115~135%
输入电流 Input current	1.5A/115V0.75A/230V	启动、上升、保持时间 Set up, rise, hold up time	800ms, 600ms, 50ms
冲击电流 AC inrush current	冷启动电流30A/115V 60A/230V Cold-start current 30A/115V 60A/230V	耐压性 Withstand voltage	1/P-O/P: 1.5KvAC1 minute 1/P-FG: 1.5KvAC1 minute 0/P-PG: 0.5KvAC1 minute
漏电流 Leakage current	<1mA/240VAC	工作温度、湿度 Working temperature	-10℃~+60℃, 20%~90%RH
直流电压可调范围 DC adjustable range	额定输出电压的 ±10% ±10% rated output voltage	重量/包装 Weight/packing	1.3kg
过载保护 Over load protection	105~135%切断输出, 自动恢复 105~135% cut down output, auto-recovery		