

HDR Series



Size:17.5*90*54.5mm

HDR-15W

型号 Type	输出 Output	差值 Tolerance	范围 Range	效率 Efficiency
HDR-15W-12V	12V 0-1.250A	±1%	120mV	83%
HDR-15W-24V	24V 0-0.63A	±1%	150mV	84%

输入电压范围 AC input voltage range	85~264VAC, 47~63HZ; 120~370VDC	过电压保护 Over-voltage protection	115~135%
输入电流 Input current	1.5A/115V0.75A/230V	启动、上升、保持时间 Set up, rise, hold up time	800ms, 600ms, 50ms
冲击电流 AC inrush current	冷启动电流30A/115V 60A/230V Cold-start current 30A/115V 60A/230V	耐压性 Withstand voltage	1/P-O/P: 1.5KvAC1 minute 1/P-FG: 1.5KvAC1 minute 0/P-PG: 0.5KvAC1 minute
漏电流 Leakage current	<1mA/240VAC	工作温度、湿度 Working temperature	-10℃~+60℃, 20%~90%RH
直流电压可调范围 DC adjustable range	额定输出电压的 ±10% ±10% rated output voltage	重量/包装 Weight/packing	0.08kg
过载保护 Over load protection	105~135%切断输出, 自动恢复 105~135% cut down output, auto-recovery		



Size:35*90*54.5mm

HDR-30W

型号 Type	输出 Output	差值 Tolerance	范围 Range	效率 Efficiency
HDR-30W-12V	12V 0-2.5A	±1%	120mV	83%
HDR-30W-24V	24V 0-1.5A	±1%	150mV	84%

输入电压范围 AC input voltage range	85~264VAC, 47~63HZ; 120~370VDC	过电压保护 Over-voltage protection	115~135%
输入电流 Input current	1.5A/115V0.75A/230V	启动、上升、保持时间 Set up, rise, hold up time	800ms, 600ms, 50ms
冲击电流 AC inrush current	冷启动电流30A/115V 60A/230V Cold-start current 30A/115V 60A/230V	耐压性 Withstand voltage	1/P-O/P: 1.5KvAC1 minute 1/P-FG: 1.5KvAC1 minute 0/P-PG: 0.5KvAC1 minute
漏电流 Leakage current	<1mA/240VAC	工作温度、湿度 Working temperature	-10℃~+60℃, 20%~90%RH
直流电压可调范围 DC adjustable range	额定输出电压的 ±10% ±10% rated output voltage	重量/包装 Weight/packing	0.25kg
过载保护 Over load protection	105~135%切断输出, 自动恢复 105~135% cut down output, auto-recovery		



Size:52.5*90*54.5mm

HDR-60W

型号 Type	输出 Output	差值 Tolerance	范围 Range	效率 Efficiency
HDR-60W-12V	12V 0-4.5A	±1%	120mV	83%
HDR-60W-24V	24V 0-2.5A	±1%	150mV	84%
HDR-60W-48V	48V 0-1.25A	±1%	150mV	86%

输入电压范围 AC input voltage range	85~264VAC, 47~63HZ; 120~370VDC	过电压保护 Over-voltage protection	115~135%
输入电流 Input current	1.5A/115V0.75A/230V	启动、上升、保持时间 Set up, rise, hold up time	800ms, 600ms, 50ms
冲击电流 AC inrush current	冷启动电流30A/115V 60A/230V Cold-start current 30A/115V 60A/230V	耐压性 Withstand voltage	1/P-O/P: 1.5KvAC1 minute 1/P-FG: 1.5KvAC1 minute 0/P-PG: 0.5KvAC1 minute
漏电流 Leakage current	<1mA/240VAC	工作温度、湿度 Working temperature	-10℃~+60℃, 20%~90%RH
直流电压可调范围 DC adjustable range	额定输出电压的 ±10% ±10% rated output voltage	重量/包装 Weight/packing	0.35kg
过载保护 Over load protection	105~135%切断输出, 自动恢复 105~135% cut down output, auto-recovery		



Size:70*90*54.5mm

HDR-100W

型号 Type	输出 Output	差值 Tolerance	范围 Range	效率 Efficiency
HDR-100W-12V	12V 0-7.1A	±1%	120mV	83%
HDR-100W-24V	24V 0-3.38A	±1%	150mV	84%
HDR-100W-48V	48V 0-1.92A	±1%	150mV	86%

输入电压范围 AC input voltage range	85~264VAC, 47~63HZ; 120~370VDC	过电压保护 Over-voltage protection	115~135%
输入电流 Input current	1.5A/115V0.75A/230V	启动、上升、保持时间 Set up, rise, hold up time	800ms, 600ms, 50ms
冲击电流 AC inrush current	冷启动电流30A/115V 60A/230V Cold-start current 30A/115V 60A/230V	耐压性 Withstand voltage	1/P-O/P: 1.5KvAC1 minute 1/P-FG: 1.5KvAC1 minute 0/P-PG: 0.5KvAC1 minute
漏电流 Leakage current	<1mA/240VAC	工作温度、湿度 Working temperature	-10℃~+60℃, 20%~90%RH
直流电压可调范围 DC adjustable range	额定输出电压的 ±10% ±10% rated output voltage	重量/包装 Weight/packing	0.45kg
过载保护 Over load protection	105~135%切断输出, 自动恢复 105~135% cut down output, auto-recovery		

HDR Series



Size:105*90*54.5mm

		型号 Type 输出 Output 差值Tolerance 范围 Range 效率 Efficiency					
HDR-150W		HDR-150W-12V	12V	0-11A	±1%	120mV	83%
		HDR-150W-24V	24V	0-6.25A	±1%	150mV	84%
输入电压范围 AC input voltage range	85~264VAC,47~63HZ;120~370VDC	过电压保护 Over-voltage protection		115~135%			
输入电流 Input current	1.5A/115V0.75A/230V	启动、上升、保持时间 Set up,rise, hold up time		800ms,600ms,50ms			
冲击电流 AC inrush current	冷启动电流30A/115V 60A/230V Cold-start current 30A/115V 60A/230V	耐压性 Withstand voltage		1/P-O/P:1.5KvAC1 minute 1/P-FG:1.5KvAC1 minute 0/P-PG:0.5KvAC1 minute			
漏电流 Leakage current	<1mA/240VAC						
直流电压可调范围 DC adjustable range	额定输出电压的±10% ±10% rated output voltage	工作温度、湿度 Working temperature		-10℃~+60℃, 20%~90%RH			
过载保护 Over load protection	105~135%切断输出, 自动恢复 105~135% cut down output, auto-recovery	重量/包装 Weight/packing		0.55kg			