

导轨式系列DIN-Rail Series **EDR Series**



Size: 32*125.2*102mm

型号 Type 输出 Output 差值 Tolerance 范围 Range 效率 Efficiency			
EDR-75W			
EDR-75W-12V	12V 0-6.3A	±2%	80mV 85%
EDR-75W-24V	24V 0-3.2A	±1%	120mV 88%
EDR-75W-48V	48V 0-1.6A	±1%	150mV 89%

输入电压范围 AC input voltage range	85-264VAC, 47-63HZ; 120-370VDC	过电压保护 Over-voltage protection	115-135%
输入电流 Input current	1.5A/115V0.75A/230V	启动、上升、保持时间 Set up, rise, hold up time	800ms, 600ms, 50ms
冲击电流 AC inrush current	冷启动电流30A/115V 60A/230V Cold-start current 30A/115V 60A/230V	耐压性 Withstand voltage	1/P-O/P: 1.5KvAC1 minute 1/P-FG: 1.5KvAC1 minute 0/P-PG: 0.5KvAC1 minute
漏电流 Leakage current	<1mA/240VAC	工作温度、湿度 Working temperature	-10°C~+60°C, 20%~90%RH
直流电压可调范围 DC adjustable range	额定输出电压的 ±10% ±10% rated output voltage	重量/包装 Weight/packing	0.55kg
过载保护 Over load protection	105-135%切断输出, 自动恢复 105-135% cut down output, auto-recovery		



Size: 40*125.2*102mm

型号 Type 输出 Output 差值 Tolerance 范围 Range 效率 Efficiency			
EDR-120W			
EDR-120W-12V	12V 0-10A	±2%	80mV 83%
EDR-120W-24V	24V 0-5A	±1%	80mV 86%
EDR-120W-48V	48V 0-2.5A	±1%	120mV 87%

输入电压范围 AC input voltage range	85-264VAC, 47-63HZ; 120-370VDC	过电压保护 Over-voltage protection	115-135%
输入电流 Input current	1.5A/115V0.75A/230V	启动、上升、保持时间 Set up, rise, hold up time	800ms, 600ms, 50ms
冲击电流 AC inrush current	冷启动电流30A/115V 60A/230V Cold-start current 30A/115V 60A/230V	耐压性 Withstand voltage	1/P-O/P: 1.5KvAC1 minute 1/P-FG: 1.5KvAC1 minute 0/P-PG: 0.5KvAC1 minute
漏电流 Leakage current	<1mA/240VAC	工作温度、湿度 Working temperature	-10°C~+60°C, 20%~90%RH
直流电压可调范围 DC adjustable range	额定输出电压的 ±10% ±10% rated output voltage	重量/包装 Weight/packing	0.65kg
过载保护 Over load protection	105-135%切断输出, 自动恢复 105-135% cut down output, auto-recovery		



Size: 60*125.2*102mm

型号 Type 输出 Output 差值 Tolerance 范围 Range 效率 Efficiency			
EDR-240W			
EDR-240W-24V	24V 0-10A	±1%	120mV 86%
EDR-240W-48V	24V 0-5A	±1%	150mV 88%

输入电压范围 AC input voltage range	85-264VAC, 47-63HZ; 120-370VDC	过电压保护 Over-voltage protection	115-135%
输入电流 Input current	1.5A/115V0.75A/230V	启动、上升、保持时间 Set up, rise, hold up time	800ms, 600ms, 50ms
冲击电流 AC inrush current	冷启动电流30A/115V 60A/230V Cold-start current 30A/115V 60A/230V	耐压性 Withstand voltage	1/P-O/P: 1.5KvAC1 minute 1/P-FG: 1.5KvAC1 minute 0/P-PG: 0.5KvAC1 minute
漏电流 Leakage current	<1mA/240VAC	工作温度、湿度 Working temperature	-10°C~+60°C, 20%~90%RH
直流电压可调范围 DC adjustable range	额定输出电压的 ±10% ±10% rated output voltage	重量/包装 Weight/packing	0.8kg
过载保护 Over load protection	105-135%切断输出, 自动恢复 105-135% cut down output, auto-recovery		



Size: 85.5*125.2*128.5mm

型号 Type 输出 Output 差值 Tolerance 范围 Range 效率 Efficiency			
EDR-480W			
EDR-480W-24V	24V 0-20A	±1%	200mV 91%
EDR-480W-48V	48V 0-10A	±1%	250mV 93%

输入电压范围 AC input voltage range	85-264VAC, 47-63HZ; 120-370VDC	过电压保护 Over-voltage protection	115-135%
输入电流 Input current	1.5A/115V0.75A/230V	启动、上升、保持时间 Set up, rise, hold up time	800ms, 600ms, 50ms
冲击电流 AC inrush current	冷启动电流30A/115V 60A/230V Cold-start current 30A/115V 60A/230V	耐压性 Withstand voltage	1/P-O/P: 1.5KvAC1 minute 1/P-FG: 1.5KvAC1 minute 0/P-PG: 0.5KvAC1 minute
漏电流 Leakage current	<1mA/240VAC	工作温度、湿度 Working temperature	-10°C~+60°C, 20%~90%RH
直流电压可调范围 DC adjustable range	额定输出电压的 ±10% ±10% rated output voltage	重量/包装 Weight/packing	1.3kg
过载保护 Over load protection	105-135%切断输出, 自动恢复 105-135% cut down output, auto-recovery		